

# SPRING COMPENSATED INJECTION SYSTEM

SPRING LOADED COMPENSATOR SYSTEM FOR FLUID INJECTION



## Description

**Standalone spring loaded 16/28/50 liter reservoir to be used for filling and injection of fluid or chemicals subsea.**

A complete system consisting of a spring loaded subsea reservoir, ROV isolation valve, hose kit and stab can be used as an add-on to the ROV for filling and injection applications. Hydraulic driven motor-pump can be added to the system to increase level of flow and pressure.

Standard setup comes with 16L reservoir, 3 meter hose kit and a ROV Isolation Valve.

## Features

- 16 / 28 / 50 liter compensators
- Manip. operated isolation valve
- Hose kit of 3 meter lengths
- Hydraulic motor-pump as optional
- Light weight POM material frame

# SPECIFICATIONS

## 16 / 28 / 50 LITER FLUID INJECTION SYSTEM

### General Technical Specifications

Type	Standalone Fluid Injection System
Part Number	113890
Dimensions	mm L675 x Ø443
Weight (in air / submerged)	kg ~60 / ~23

### Hydraulic

Min Pressure	Bar 0,09
Max Pressure	Bar 0,44

Fluid Compatibility	Type Mineral Oil, Water Glycol and Citric Acid
Fluid tank size	Liter 16 / 28 / 50

Connections - 4 off	JIC #8
Connection output supply hose	JIC #8

### General Features

Depth rating	MSW 3000
--------------	----------

