

STANDARD TORQUE TOOL

ROV INTERVENTION
CLASS 1-4
2700 NM



Description

The hydraulic Class 1-4 torque tool has been designed in tradition of providing our customers a simple, rugged and reliable product.

The standard Class 1-4 Torque Tool comes with an integral turns display counter for visual read-out of turns feedback.

The Torque Tool can be supplied with a surface Test Jig for calibration prior to sub-sea operation. The read-out unit provides a torque display in either Nm or ft-lbs.

Features

- Max torque output 2700 Nm
- ISO 13628-8 & API 17D
- Max hydraulic pressure 170 bar
- Max flow 20 L/min
- Spring latches
- Turn counter

■ The specification details are illustrative for marketing purposes only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement.

Envirent AS, Hattelandsveien 92, 4353 Klepp Stasjon, +47 477 77 500 post@envirent.no

SPECIFICATIONS

STANDARD TORQUE TOOL

General Technical Specifications

| | |
|-----------------------------|--------------------------------|
| Type | Standard Torque Tool Class 1-4 |
| Part Number | 103295 |
| Dimensions | mm L670 x 200 x 369 |
| Weight (in air / submerged) | kg ~42 / ~36 |

Hydraulic

| | |
|---------------------|----------|
| Max. Input Pressure | Bar 170 |
| Max. Input Flow | L/min 20 |

| | |
|---------------------------|--------|
| Connection ROV pressure A | JIC #8 |
| Connection ROV pressure B | JIC #8 |
| Connection ROV drain | JIC #6 |

General Features

| | |
|--------------|----------|
| Depth rating | MSW 3000 |
|--------------|----------|

