

TORQUE WRENCH SYCLONE 3

ROV INTERVENTION
TORQUE WRENCH
1000-4000 NM



Description

ROV operated lightweight torque wrench tool for tightening or retrieval of bolts.

The torque wrench is a small, continuously rotating torque tool with a lot of force. Rotate both directions with high precision and speed. Can be fitted with a wide range of bolt sockets. Comes with ROV fishtail handle as standard.

Features

- Drive 1" square
- Interchangeable sockets (client specification)
- Torque range 1000 - 4000 Nm
- Input pressure 20 - 170 bar
- Max 20 RPM @ 40 L/min
- Weight 12 kg
- Fishtail handle as standard

□ The specification details are illustrative for marketing purposes only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement.

Envirent AS, Hattelandsveien 92, 4353 Klepp Stasjon, +47 477 77 500 post@envirent.no



SPECIFICATIONS

TORQUE WRENCH SYCLONE 3

General Technical Specifications

Type	Torque Wrench Syclone 3
Part Number	108173
Dimensions	mm L550 x Ø200
Weight (in air / submerged)	kg ~15 / ~12

Hydraulic

Max. Input Pressure	Bar 170
Max. Output Torque	Nm 4000

Connection ROV pressure A	JIC #8
Connection ROV pressure B	JIC #8

General Features

Depth rating	MSW 3000
--------------	----------