COMPENSATOR 13,5 LITER

WITH OR WITHOUT SENSOR LIGHTWEIGHT SUB-ATLANTIC



Description

The 13,5L compensator is a lightweighted and proven compensator. It is mainly used to maintain a raised pressure in a fluid circuit related to ambient at all water depths.

Compensator can be delivered with or without volume sensor. Without sensor you can use the compensator at full ocean depth. With sensor maximum depth is limited to sensor specifications.

Features

- Solid and Reliable Design
- Lightweight
- Optional Sensor
- Spring Loaded
- Adjustable Pressure Relief Valve



• The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, post@envirent.no

Specifications

13,5L Compensator

General Technical Specifications

Type Capacity Dimensions Ø x H Weight in air (full of oil) Weight in Water (full of oil) Pressure when full Pressure when near empty Hydraulic Connection

Without Sensor

13,5L Compensator 13,1 Liter 285 x 500 mm 28,3 kg 7,6 kg 0,48 Bar 0,24 Bar BSPP or SAE

With Sensor

13,5L Compensator 13,3 Liter 285 x 500 mm 29 kg 7,9 kg 0,48 Bar 0,24 Bar BSPP or SAE



The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, post@envirent.no