

# STAB Ø35MM QP-10K- INTERV W/CV BSP 3/8"

PRESSURE RATED TO 690 BAR(10K)  
FIELD PROVEN  
WITH CHECK VALVES



## Description

The Ø35mm Hot Stab is made accordingly to API 17H Type 1 and comes in different types and configurations to suit a wide range of applications.

Ø6 bores for maximum flow and minimum pressure drop. Pressure tested to 1.5 x design pressure. Designed for flow up to approximately 25 l/min.

ROV or diver operated. Low mating force and easy entering, integrated flexjoint between stab and D-handle. Locking mechanism for stab available for critical applications.

Available in 1,2,3 and 4-port configurations for maximum flexibility. 1-4 ports receptacles, pressure stabs, dummy stabs and parking receptacles available.

## Typical Operations

- ▣ Topside Tooling Applications
- ▣ Subsea Operations
- ▣ Function Testing
- ▣ Flushing

## Features

- ▣ Field Proven
- ▣ Integrated with Check Valves
- ▣ Compact Design
- ▣ Service and User Friendly
- ▣ Robust

# Specifications

STAB Ø35MM QP 10K INTERV W/CV BSP 3/8"

## General Technical Specifications

Type	Hot Stab Ø35 QP 10K w/cv
Part No	N/A
Dimensions L x W x H	441 mm x 70 mm x 120 mm
Design Standard	4,2 kg

## Hydraulic

Pressure Rated	690 Bar
Hydraulic Input #1	3/8" BSP
Hydraulic Input #2	3/8" BSP
Hydraulic Input #3	3/8" BSP
Hydraulic Input #4	3/8" BSP

