

# STAB Ø80MM SP-10K- INTERV WECO 1502 2"

PRESSURE RATED TO 690 BAR(10K)  
FIELD PROVEN  
WITH CHECK VALVES



## Description

The Ø80mm Hot Stab program is optimized with respect to maximum flow and designed for RFO activities and well intervention. Combining high flow and high pressure makes it perfect for activities related to pigging and testing. Designed after API 17H ISO13628-8 and comes in different types and configurations to suit a wide range of applications.

Ø8 bores for maximum flow and minimum pressure drop. Pressure tested to 1.5 x design pressure.

ROV or diver operated. Low mating force and easy entering. Integrated handle and integrated for 2" 1502 Weco connector. Integrated with swivel and J-lock.

## Typical Operations

- ▣ Topside Tooling Applications
- ▣ Subsea Operations
- ▣ Function Testing
- ▣ Flushing

## Features

- ▣ Field Proven
- ▣ Integrated with Check Valves
- ▣ Compact Design
- ▣ Service and User Friendly
- ▣ Robust

# Specifications

STAB Ø80 SP-10K-INTERV WECO 2"

## General Technical Specifications

Type	Hot Stab Ø80 SP-10K-Interv WECO 1502 2"
Part No	N/A
Dimensions L x W x H	537 mm x 136 mm x 136 mm
Design Standard	15,7 kg

## Hydraulic

Pressure Rated	690 Bar
Hydraulic Input #1	2" 1502 WECO Female

