

RECEPTACLE Ø43MM TP- 10K-INTERV W/CV BSP 1/2"

PRESSURE RATED TO 690 BAR (10K)
FIELD PROVEN
WITH CHECK VALVES



Description

Receptacle and hot stabs come with integrated check valves as a default for minimum fluid spill and water ingress during operations.

The Receptacle and Hot Stabs are designed to maximize the flow capacity and minimum pressure drop.

Built after API17H, Type 1 design. Available in 1,2,3 and 4-port configurations for maximum flexibility. 1-4 Ports Hot Stabs, Dummy Stabs and Parking Receptacles are available. The Hot Stab/Receptacle system can also be fitted with a lock-system.

Typical Operations

- ▣ Topside Tooling Applications
- ▣ Subsea Operations
- ▣ Function Testing
- ▣ Flushing

Features

- ▣ Field Proven
- ▣ Integrated with Check Valves
- ▣ Compact Design
- ▣ Service and User Friendly
- ▣ Robust



Specifications

Ø43 ROV RECEPTACLE TP-10K-INTERV W/CV ½" BSP

General Technical Specifications

Type	ROV Receptacle
Part Number	N/A
Dimensions L x W x H	200 mm x Ø65 mm x Ø65 mm
Weight in air	6,6 kg

Hydraulic

Max Input Pressure	690 Bar
Max Output Pressure	690 Bar
Max Input Flow	25 L/min
Max Output Flow	25 L/min

Connection Port 1	½" BSP
Connection Port 2	½" BSP
Connection Port 3	½" BSP

