


# PRESSURE RELIEF VALVE

PRV  
VALVE  
SERIES



## Description

A compact, highly accurate, direct acting pressure relief valve. Factory preset to 0.8 Bar or 1,5 Bar crack pressure. Internal adjustments provides tamper proof safety against inadvertent pressure changes.

## Features

- Accurate and repeatable crack pressure
- 100% Factory and preset testing
- Wide Range of fluid compatibility
- Zero leakage to 95-98% of set pressure
- Excellent re-seal performance
- Compact size
- Custom pressure setting on request

## General Technical Specifications

Type	Pressure Relief Valve
Part Number	Various, see table below
Body Material	AISI316L / NBR
Fluid Compatibility	Mineral Oil, Water Based Glycol and Seawater
Operating Temperature	-10°C/ + 60°C (14°F / 122°F)
Cracking pressure	0,8 or 1,5 Bar

## Ordering Codes

PRV 1/4" BSP - 0,8 Bar Crack Pressure  
PRV 1/4" BSP - 1,5 Bar Crack Pressure  
PRV 1/2" BSP - 0,8 Bar Crack Pressure  
PRV 1/2" BSP - 1,5 Bar Crack Pressure

Part Number: V100382  
Part Number: V100559  
Part Number: V100391  
Part Number: V100383

## Dimensions

