SYCLONE 1 TORQUE TOOL

ROV OPERATED 50-550 NM 20-100 BAR



Description

The Syclone 1 is a ROV operated torque tool with a lot of force. It can rotate both ways with high precision and speed.

Torque is fully adjustable and with a precision of \pm 3%. Can be ordered with a standard reaction arm, or you can get one custom made.

Typical Operations

- Tighten bolts
- Loosen bolts

Features

- □ 50-550 Nm
- □ ± 3% torque precision
- □ ³⁄₄" square drive
- Custom reaction arm.



The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, post@envirent.no

Specifications

Syclone 1 Torque Tool

Description

Type Model Dimensions L x W x H Weight

Technichal

Work Pressure (Continuous) Peak Pressure (Max 6 seconds) Torque Range Drive Size Max rpm Max Flow Torque Precision

Hydraulic

Connection Pressure Connection Return Hose Dimension Hose Length Subsea Torque Tool Syclone 1 250 mm x 180 mm x 120 mm 4 kg

20-100 Bar 140 Bar 50-550 Nm 3/4" Square 42 rpm @ 20 l/min 20 l/min ± 3%

JIC #6 JIC #6 3/8" 4 meter



The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, post@envirent.no