

HP690 INTENSIFIER PANEL

SUBSEA TOOLS

INTENSIFIER PANEL



Description

The HP690 Hydraulic Intensifier Panel is a compact, lightweight solution ideal for ROVs with limited payload space. It is compatible with 2-port hotstabs for quick and easy connection.

A factory-set relief valve and integrated safety circuit automatically bleed excess pressure, while dual pressure gauges provide accurate, real-time readings.

Versatile for operation at any depth, the HP690 features an industry-standard minibooster and proven Webtool engineering, delivering powerful, reliable performance in subsea applications.

Features

- Integrated safety circuit
- Corrosion resistant
- Compact
- Robust
- Dual pressure gauges



Specifications

HP690 Intensifier Panel

General Technical Specifications

Type	HP690 Intensifier Panel
Part Number	980507
Dimensions L x W x H	252 mm x 153 mm x 144 mm
Weight in air	10.7 kg

Hydraulic

Max Input Pressure	172.5 Bar (2,500psi)
Max Output Pressure	690 Bar (10,000psi)
Max Input Flow	14 L/min
Max Output Flow	2 L/min

Connection ROV Pressure	JIC #4
Connection ROV Return	JIC #4
Connection Cutter Pressure	JIC #4
Connection Cutter Return	JIC #4

